

SMC AB



SMC XS / XE

Hydraulhammare

- Ljuddämpad av olja/gas typ



Model	XS-70	XS-100	XS-200	XS-300	XS-500
Driftsvikt (kg)	87	174	246	344	547
Längd (mm)	924	1077	1198	1411	1659
Mejseldiameter (mm)	45	56	65	70	85
Oljetryck (bar)	81~122	91~122	122~163	122~163	132~173
Oljeflöde (l/min)	14~30	20~40	30~60	35~90	40~90
Slagenergi (joule)	139	212	537	825	1027
Slaghastighet (bpm)	650~1200	500~1200	500~1000	450~800	450~750
Bärmaskinens vikt (ton)	0,5~1,7	1,5~3,5	2,5~4,5	3~9	6~12
Tryck, Kolvackumulator (bar)	9	9	10	15	15

Model	XS-1000	XS-1500N	XS-1600N	XS-2000N	XS-3000N
Driftsvikt (kg)	1050	1375	1651	2480	2950
Längd (mm)	1990	2096	2179	2452	2658
Mejseldiameter (mm)	99	132	142	152	157
Oljetryck (bar)	150~170	150~180	150~180	150~180	150~180
Oljeflöde (l/min)	80~110	110~150	110~150	150~190	170~250
Slagenergi (joule)	1837	3204	3918	5321	6435
Slaghastighet (bpm)	450~700	360~480	360~480	340~460	320~450
Bärmaskinens vikt (ton)	10~17	14~22	16~24	22~35	28~40
Frekvensreglering	Nej	Ja	Ja	Ja	Ja
Tryck, kolvackumulator (bar)	15	16~18	16~18	16~18	16~18
Tryck, membranackumulator (bar)				55	55

Model	XE-3500	XE-4500	XE-7000	XE-9000
Driftsvikt (kg)	3500	4500	7000	8300
Längd (mm)	2921	3195	4236	4591
Mejseldiameter (mm)	165	180	205	225
Oljetryck (bar)	165~185	165~185	165~185	155~185
Oljeflöde (lpm)	180~260	230~330	320~420	380~480
Slagenergi (joule)	6000~7600	7900~10 400	10 000~13 000	13900~18500
Slaghastighet (bpm)	310~560	250~480	250~450	250~425
Bärmaskinens vikt (ton)	30~40	40~70	65~100	80~120
Frekvensreglering	Ja	Ja	Ja	Ja
Tryck, kolvackumulator (bar)	16~18	16~18	16~18	17~19
Tryck, membranackumulator (bar)			60	

SMC AB

T: +46 (0)8-647 04 03
 F: +46 (0)8-647 04 25
 Sadelmakarvägen 11B | PL 530
 SE-146 33 Tullinge | SWEDEN
info@demolering.se www.demolering.se